




MODEL 32




MODEL 32-W



BELOW CEILING




WALL OR POST



ABOVE CEILING



ABOVE FLOOR




WALL



BELOW FLOOR

The new Eco Hose-Reels fill every reel need. Can be installed on the floor, ceiling or wall. Base easily mounted in any one of seven different positions. Hose outlet and air inlet adjustable to any one of four positions. For wall installations where space is a factor, the reel base can be removed and the reel mounted flush with the wall.

The selective stop retains the 25-foot hose at desired length. When not in use, the hose is out of the way and always instantly accessible. Combined with Model 15 or 37 High-Speed Tiremeters, the Air-Reel offers efficient automatic tire service. The Water-Reel provides a reliable and convenient water outlet that will serve many purposes. Shipping weight, Model 32, approx. 91 lbs. Shipping weight, Model 32-W, approx. 98 lbs.




MODEL EH-2156

Highly efficient V-type two stage Air Compressor suitable for use in average service stations and garages. One and one-half horse power electric motor. Chatter-proof Cloz-or-open type check valve. National Board type A.S.M.E. 62 gallon capacity tank.

Dimensions of unit: height, 39"; length, 58"; width, 22". Shipping weight approx. 710 lbs.

MODEL EH-238 Large capacity V-type two stage Air Compressor for use where more than average air service is needed. Employs three horsepower motor with thermal protection. Chatter-proof Cloz-or-open type check valve. National Board type A.S.M.E. 80 gallon capacity tank.

Dimensions of unit: height, 42½"; length, 75"; width, 23". Shipping weight approx. 945 lbs.




MODEL EH-238

NOTE: Motor voltage and current ratings desired on any model Air Compressor must be specified at the time of order so that the motor may be wired correctly at our factory.

MODEL EV-2346 Vertical V-type two stage Air Compressor for installation where space is a factor. Three-quarter horsepower motor with thermal protection. Chatter-proof Cloz-or-open type check valve. National Board type A.S.M.E. 62 gallon capacity tank.

Dimensions of unit: height, 72"; length, 42"; width, 27". Shipping weight approx. 675 lbs.



MODEL EV-2346