




**MODEL 58**

Meets the demand for a good looking, high-speed pedestal air unit at a price well within the reach of the average station. A 5 to 45 lb. mechanism, with straight air release, is standard equipment. The same 20 to 80 lb. mechanism used on Model 15 can be supplied upon request. Shipping weight approx. 105 lbs.




**MODEL 37**

For wall or post mounting indoors or outdoors — embodies the same high-quality features as Model 38. Unexcelled for auxiliary air lines of larger service stations, tire shops and fleet owners. Shipping weight approx. 54 lbs.



**MODEL 15**

Wall Type unit serving those who require higher than average pressure . . . 20 to 80 lbs. without provision for direct tank pressure. A highly efficient unit at a low price. Also supplied with a 5 to 45 lb. mechanism with provision for obtaining direct tank pressure. Shipping weight approx. 34 lbs.



**MODEL 39**

Distinguished for their beauty and performance. Each of these models utilizes the well known automatic inflation mechanism with double acting bells that cease ringing when the exact needed air pressure is reached. A spring actuated hose reel gently and automatically retracts the 25' hose. Locking arrangement prevents theft of hose. Light illuminates dials from within.



**MODEL 40**

Model 39 differs from the Model 40 only in that no AIR globe and globe adapter is furnished. Overall height, Model 39, 52"; shipping weight approx. 264 lbs. Overall height, Model 40, 67"; shipping weight approx. 268 lbs.